MOTION MOTORISED CURTAIN TRACKS





dist it.

DC1660

Specification:

Blind Designs Motion Motorised track is available as a heavy duty track, controlled by a 60kg capacity 220v motor. Brackets are available to suit Top Fix, Face Fix or Double Face Fix installation applications.

The track is available in both GLIDE and RIPPLE options. The Ripple Runners are available in a variety of fullness options. You can choose between the press stud and snap tape or hook tape options. The master carrier is driven by a low friction rubber belt, and different arms are available for the master carrier to suit your application.

FEATURES:

- Heavy duty design
- A variety of runner and installation configurations to choose from
- Built in receiver with a variety of remote controller options available
- Compatible with various home automation systems
- Can stop at any point with the remote, or else motor stops when it meets resistance
- Gently pull the curtain to start the motor running if the remote is not accessible

Time

- Curtains can be operated by hand when the power is off

urrent



Top Fix Bracket

Face Fix Bracket

Curtain Motor





Rubber Belt

Remote





Outline



		Safety C Weight	Rated to	Open/Cl Speed	Rated C	Running	Degree	Max Nur of Turns	Track Le	Weight
Technical Data		(Kg)	(W)	(cm/sec)	(A)	(min)	(IP)	(Turn)	(m)	(kg)
220V / 60 Hz						Product C	ertificate		@ CE	RoHS
DT52EN Electronic Radio	DT52EN-75/20	60	75	20	0.34	4	40	00	<12	1.2

ose

rque

Curtain

Tubular Motor Nameplate

Inner Structure Picture

DT	52	EN -	75	/ 20
DOOYA Curtain Motor	Demension Code	Electronic Radio	Rated Torque (W)	Open/Close Speed (cm/sec)





Motor End

ength

Motor Head

of on nber